

NITRO *Stinger*®

BY

Express



The Express NitroStinger uses a Nitrogen over Oil Accumulator in its fully self-contained hydraulic loading system. This allows the NitroStinger to maintain a constant load on the stinger axle over virtually any terrain. The axle has the capability of maintaining this load through over **2 feet** of travel. In addition, the hydraulic system can be used to lift the NitroStinger axle off the ground for backing up.

of Axles: 1

GVWR: 25,000 pounds

Axle Spread: 10' or 14'1"

Couples to: Most Makes of Trailers
Many pieces of Heavy Equipment

OAL: 15'

OAW: 102"

Weight: ~4300 pounds

Suspension: Air Ride

Tires: 275/70R22.5 Yokohama RY103
255/70R22.5 Yokohama RY023
275/70R22.5 Goodyear G104 RST
255/70R22.5 Goodyear G104 RST

Hydraulic System Power Source:
6.5hp Honda Engine OR
Air Powered Hydraulic Pump

Paint Color: Black is Standard
Can match most colors

Options: Black Poly Fenders



AUTHORIZED DEALER

WW TRAILERS INC.



5000 NE COLUMBIA BLVD
PORTLAND, OR 97218

866-600-6645

Express

Express Welding, Inc.
2525 14th Avenue North
Escanaba, MI 49829

906-786-8808 (P)
906-786-6165 (F)
info@Express-Welding.com
www.Express-Welding.com